

# TECHNICAL DATA SHEET

## NASNDD900

NDD 900 DRY VACUUM 1200w/1.6 HP/2 SP FINE DUST 45.4 LT



- The dual motor NDD900 incorporates our patented Micro-Flo or Hepa-Flo vacuum bags along with a Microtex filter as standard equipment ensuring optimum filtration.

These machines are specially designed for use with concrete dust, drywall dust, wood dust and chimney soot along with just about any other fine non explosive particulate that can harm the respiratory system.

They meet or exceed all OSHA regulations regarding silica crystalline recovery as a repairable dust under OSHA regulation 1910.1000.

**Vacuum Tank Capacity:**12 Gallon

**Vacuum Motor Watts:**2 x 800W

**Vacuum Motor HP:**2.14 Total

**Vacuum Motor Stages:**2 Stage

**Number of Motors:**2

**Speeds:**1 Speed

**Airflow (cfm):**200 CFM

**Waterlift:**100"

**Noise Level dB(A):**67 DB(A)

**Head Construction:**STRUCTURAL FOAM

**Hose Length:**10'

**Power Cord Length:**42'

**Standard Filter:**TRITEX COMBINATION + MICROFLO OR HEPAFLO

**Standard Filtration:**:3 MICRON @ 99.6% EFF.

**Tank Construction:**STRUCTURAL FOAM

**Weight:**49 LBS