

TECHNICAL DATA SHEET

NASNDS570

NDS 570 DRY VACUUM 1200w/1.6 HP/1 SP FINE DUST 18.9 LT



- The NDS 570 incorporates our patented Micro-Flo or Hepa-Flo vacuum bags along with a Microtex filter as standard equipment ensuring optimum filtration. These machines are specially designed for use with concrete dust, drywall dust, wood dust and chimney soot along with just about any other fine non explosive particulate that can harm the respiratory system.

- They meet or exceed all OSHA regulations regarding silica crystalline recovery as a repairable dust under OSHA regulation 1910.1000.

- The patented air flow technology used in the design of the tank ensures a consistent uninterrupted flow regardless of how full the bag is.

Vacuum Tank Capacity:5 Gallon

Vacuum Motor Watts:1200W

Vacuum Motor HP:1.6 HP

Vacuum Motor Stages:2 Stage

Number of Motors:1

Speeds:1 Speed

Airflow (cfm):100 CFM

Waterlift:110"

Noise Level dB(A):64 DB(A)

Head Construction:STRUCTURAL FOAM

Hose Length:10'

Power Cord Length:42'

Standard Filter:TRITEX COMBINATION + MICROFLO OR HEPAFLO

Standard Filtration:.3 MICRON @ 99.6% EFF.

Tank Construction:STRUCTURAL FOAM

Weight:44 LBS