


Silco

Floor Sealer

TECHNICAL DATA SHEET

DESCRIPTION



SILCO floor sealer is an exceptionally tough and high solids polymer formulation, developed to provide the most porous imperfect floors and high-traffic areas with a durable undercoat, a uniform surface and good adhesion to the substrate for all types of today's advanced floor finishes.

SILCO is applied directly over the flooring substrate before the layers of floor polish to protect and level floor surfaces. Allowing floor finish for better aesthetics and a more sanitary condition, helping to fill pores and valleys where germs grow.

SILCO is designed to be a tough "semi permanent" base coat, whose high solids strength protects the flooring substrate from pedestrian and vehicular traffic and cleaning chemicals damage.

SILCO superior formulation means longer life and fewer recoats. It dries to colorless, transparent, flexible film that will not discolor or yellow with time and offers a solid base to all types of floor finishes.

DIRECTIONS FOR USE

Strip floor with Gilco **ZIP** or **GT-18** super stripper. Rinse floors with clean water, changing rinse water frequently to prevent re-depositing of dirt and stripper residue. Allow floor to dry before applying **SILCO**.

Application:

Use new or clean mop, or lamb's wool applicator and a clean bucket.

Saturate mop with **SILCO**

Press mop into wringer to remove excess finish. Do not over wring sealer mop.

Allow **SILCO** to dry 20 minutes under normal room conditions.

Consult a GILCO representative for more information.

PROPERTIES

Appearance :	Liquid
pH (1% solution) :	~8.5
Solubility :	Instant
Odor :	Light Ammonia
Color	Off White

PRECAUTIONS

PACKAGING CODE

4 L
 4 x 4 L
 20 L
 210 L

Never pour partially used finish back into the original container; it would contaminate the remaining product.
 Do not use on food contact surfaces. Do not store in food processing or food storage areas. Do not contaminate food products.